

# GL34A THRU GL34M


## SURFACE MOUNT GLASS PASSIVATED RECTIFIERS

Reverse Voltage - 50 to 1000 V

Forward Current - 0.5 A

### Features

- Low power loss, high efficient
- High surge current capability
- Low forward voltage drop
- For use in low voltage, high frequency inverters, free wheeling application
- Guarding for over voltage protection



MiniMELF (DO-213AA) Plastic Package

### Mechanical Data

- Case: MiniMELF(DO-213AA), molded plastic body
- Terminals: Plated terminal
- Polarity: Color band denotes cathode end
- Mounting Position: Any


### Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Parameter	Symbols	GL34A	GL34B	GL34D	GL34G	GL34J	GL34K	GL34M	Units
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at $T_T = 75\text{ }^\circ\text{C}$	$I_{F(AV)}$	0.5							A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	$I_{FSM}$	25							A
Maximum Forward Voltage at 0.5 A	$V_F$	1.1							V
Maximum Reverse Current at Rated DC Blocking Voltage $T_A = 25\text{ }^\circ\text{C}$ $T_A = 125\text{ }^\circ\text{C}$	$I_R$	5 250							$\mu\text{A}$
Typical Junction Capacitance <sup>1)</sup>	$C_J$	4							pF
Typical Thermal Resistance <sup>2)</sup>	$R_{\theta JA}$	125							$^\circ\text{C/W}$
Operating and Storage Temperature Range	$T_j, T_{stg}$	- 65 to + 150							$^\circ\text{C}$


<sup>1)</sup> Measured at 1 MHz and applied reverse voltage of 4 V D.C

<sup>2)</sup> Thermal resistance from junction to ambient.




**SEMTECH ELECTRONICS LTD.**

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)




# GL34A THRU GL34M


DERATING CURVE FOR OUTPUT RECTIFIER CURRENT





MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



TYPICAL JUNCTION CAPACITANCE



**SEMTECH ELECTRONICS LTD.**  
 (Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)

